

Web Results 1 - 30 of about 5,500 for sending a push request containing client ID, IP address, TCP/IP port number for out of band direct connection to a specific node on P2P network to upload a file associated with file index. (0.69 seconds)

Show options...

1. [PDF] Peer-to-Peer Networks for Content Sharing

File Format: PDF/Adobe Acrobat - [Quick View](#)

by CH Ding - Cited by 12 - [Related articles](#)

A number of P2P networks for file sharing have been IP address of a client sharing the requested file. requested to push the file with index File_Index. Drop a connection to a node if it has not been able to receive or send the message for Used to request network statistics from Index Nodes. ... [www.buyya.com/papers/P2PbasedContentSharing.pdf](#) - [Similar](#)

2. [PDF] Title: P2P Networks for Content Sharing

File Format: PDF/Adobe Acrobat - [Quick View](#)

by CH Ding - 2004 - Cited by 6 - [Related articles](#)

Client_Info is a string containing the client version info. person sharing the file can only make outgoing TCP connection because of the firewall port, IP address, the number of files shared, and the number of kilobytes shared. Super Node, who will in turn broadcast that same query out to all other ... [arxiv.org/pdf/cs/0402018](#)

3. FREJON: KaZaA P2P FastTrack Internals - File Formats

Default KaZaA file service IP-port is 1214. Can be NULL for a file service behind a ... In these cases the destination node sends a PUSH Request to his supernode. Client nodes connect to the FastTrack network with a single ... When no one responded to such an UDP-probe, connections over TCP/IP are tried next. ... [members.home.nl/frejon/55/ft/KazaaFileFormats.html](#) - [Cached](#)

4. [PDF] Unstructured P2P networks by example: Gnutella 0.4, Gnutella 0.6

File Format: PDF/Adobe Acrobat - [Quick View](#)

by S Ertel - [Related articles](#)

a file sharing protocol for decentralized P2P networks ... ing not only an IP address and port, but also the number of files and kilobytes to be ... a direct TCP/IP connection over HTTP using the pa- ... accomplished by sending a PUSH message, indicating a peer-to-peer network where every node act in a client ... [ra.crema.unimi.it/turing/MATERIALE/.../Ceravolo_file2.pdf](#) - [Similar](#)

5. Computer Networks and the Internet

Jan 1, 2010 ... Make sure you give the hostname and the file name parts of the URL. Suppose the IP address for the associated URL is cached in your ... Persistent HTTP with pipelining In-band versus out-of band ... An alternative design would be for Bob to establish a direct TCP connection with Alice and send ... [www.docstoc.com/docs/.../Computer-Networks-and-the-Internet/](#) - [Cached](#)

6. Packet Forgery By ISPs: A Report on the Comcast Affair ...

Oct 19, 2007 ... Users whose ability to upload or find and download a rare file on the ... By arbitrarily using RST packets in a manner at odds with TCP/IP standards, ... to limit the amount of traffic that P2P software transmits on their network, But if Comcast were encountering severe DOCSIS request-to-send ... [www.eff.org › Our Work › Whitepapers](#) - [Cached](#) - [Similar](#)

7. gtk-gnutella - The Graphical Unix Gnutella Client

Mar 29, 2009 ... Loop through the **TCP push-proxies** more quickly until one can ...
Upload statistics now record the file's SHA-1, so that we can ... Added more entropy
to the **random number seed**. ... No longer **send SHA-1 queries** on the Gnutella
network. ... Updated list of **hostile IP address ranges**, Geo-IP data, ...
gtk-gnutella.sourceforge.net/ - [Cached](#) - [Similar](#)

8. [PDF] Microsoft PowerPoint - 8.P2P [Compatibility Mode]

File Format: PDF/Adobe Acrobat - [Quick View](#)
Apr 9, 2009 ... A **client** interested in a file contacts the **tracker specified** in the The
QueryHit contains **IP address** and **port number** of the peer who sent it. ▀ Files are
downloaded **out-of-network**. ▀ A **direct connection** between the source and target ...
A peer can **request a file push** by **sending a Push request** ...
www.systems.ethz.ch/education/courses/fs09/aen/lectures/8.P2P_4x1.pdf

9. LNAI 3601 - Distributed Hash Queues: Architecture and Design

by C Yoshikawa - [Cited by 6](#) - [Related articles](#)
Address Translated (NATed) peers in a **P2P network**. DHQs are an a **node ID**
which consists of a 160-bit key and a **IP address**. ... for a DHQ **client** is that it must
support **TCP/IP** and be capable of **sending** ... **node** is found, the NATed **node** opens
up a **socket connection** to the gateway over a well-known **port number**. ...
www.springerlink.com/index/B469T054453U1848.pdf

10. Network, Networking Technology, Data Communication Terms, Glossary ...

Jan 28, 2010 ... **Push technologies** which **send** information to subscribers are another
form for narrowcasting. **Network Number** is the part of an **IP address** that
specifies the ... In the **TCP** and **UDP** protocols used in computer networking, a **port**
is **New Technology File System (NTFS)** is an enhanced file system ...
www.networkdictionary.com/networking/in.php - [Cached](#) - [Similar](#)

11. Eng MBA: a. Computer Network And Internet

File Server: Provides a location for the shared storage of computer files **Internet**
Addresses are currently in IPv4, or in 32-bit **number** that can ... An intranet is a
private **TCP/IP** computer **network** that is contained within an organization. **Pure**
P2P: It is a **direct connection** between computer to computer, ...
engmba.wikidot.com/a-computer-network-and-internet - [Cached](#) - [Similar](#)

12. SampleCaptures - The Wireshark Wiki

ipv4_cipso_option.pcap (libpcap) A few **IP** packets with CIPSO option. **PPP-config**.
cap LCP and IPCP configuration of a **Direct Cable Connection (WinXP)** ... Note that
the examples uses **port number** 24209, which must be configured in the protocol ...
File: nntp.pcap A capture of the NNTP protocol (a KNode client ...
wiki.wireshark.org/SampleCaptures - [Cached](#) - [Similar](#)

13. [PDF] Analysis of Peer-to- Peer Network Security using Gnutella - CiteSeerX

File Format: PDF/Adobe Acrobat - [Quick View](#)
by D DeFigueiredo - [Cited by 7](#) - [Related articles](#)
and the link speed of the responding **node**. **Push** is used to **upload a file** to clients ...
containing as payload a 13-byte descriptor. {port, **IP address**, **number of** ... the
Gnutella header, sends {**node ID**, **File**, **Index**, **IP address**, **port**} to the ... origination
node. The serving **node** then starts a **TCP connection** back to ...
citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.83.5994&rep...

14. [PDF] P2P Security

File Format: PDF/Adobe Acrobat - [Quick View](#)
by A Friedman - [Cited by 3](#) - [Related articles](#)
namespace, and the **IP address** of the **node** belonging to that identifier. **client** has
an incentive to **upload** what it has to other machines, ... A reduction in demand for a
file will limit the **number** of BitTorrent clients that will **Out-of-band** A message that

is not passed across the **network** in question, ...
allan.friedmans.org/papers/IP2Psecurity.pdf - [Similar](#)

15. [Troytec Network+ Exam](#)

Each **address** is a unique 12-digit hexadecimal **ID number**, which is hard coded to
If no **address** exists in the pool, the client cannot initialize **TCP/IP**. The exhibit shows two boxes that have in and out **ports** and many machines To **send a formatted file** to a Novell **network** printer from DOS you would use ...
www.scribd.com/doc/2228334/Troytec-Network-Exam - [Cached](#) - [Similar](#)

16. [GNUnet FAQ](#)

While **peer-to-peer networks** can theoretically provide better performance than dedicated for a **client-only** system, or you might not care about anonymous **file-sharing**. ... **network address** (say IP and port) together with a timestamp and **send** this, Once you have the process **ID** (2-5 digit number), start gdb. ...
gnunet.org/faq.php3?xlang=Polish - [Cached](#)

17. [PDF] The Teredo Protocol: Tunneling Past **Network Security** and Other ...

File Format: PDF/Adobe Acrobat - [Quick View](#)
by J Hoagland - [Related articles](#)
internal **IP address**. If either the source address or source port does not match a
Client port number: This is somewhat sensitive because the Teredo protocol ... **direct** Internet connectivity inherently reveal a way to reach the **node** via One way for an **attacker** to convince the **client** to **send out** multiple ...
www.symantec.com/avcenter/reference/Teredo_Security.pdf - [Similar](#)

18. [PPT] [Review for Quiz-1](#)

File Format: Microsoft Powerpoint - [View as HTML](#)
sends "slow down **sending rate**" when **network** congested identifier includes both **IP address** and **port numbers** associated with process on host. ... Server opens another **TCP data connection** to transfer another **file**. ... Alice runs **P2P client** application on her notebook computer; Intermittently connects to ...
www.csc.gatech.edu/~copeland/3076/slides/Quiz-1%20Review.ppt

19. [PPT] [TCP](#)

File Format: Microsoft Powerpoint
Identifier includes both the **IP address** and **port numbers** associated with the
HTTP client receives response message containing html file, displays html.
Control connection: "out of band"; FTP server maintains "state": current ... message from client to server, port 25; direct transfer: **sending** server to ...
comnet.kaist.ac.kr/~yhlee/CN_Un.../lec-cn3-application_layer-2006.ppt

20. [The World of Peer-to-Peer \(P2P\)/Chapter P2P Implementations ...](#)

Feb 12, 2010 ... An IRC **client** is a program that connects to a given IRC server in order **Direct connect** is a **peer-to-peer** file sharing protocol/**network** but it ... It has numerous features such as a plugin to block **IP addresses** **P2P** wireless **network**, where every peer (**node**) is connected to its neighbors. ...
[en.wikibooks.org/...Peer-to-Peer_\(P2P\)/Chapter_P2P_Implementations](http://en.wikibooks.org/...Peer-to-Peer_(P2P)/Chapter_P2P_Implementations) - [Cached](#)

21. [PPT] [Part I: Introduction](#)

File Format: Microsoft Powerpoint - [View as HTML](#)
Dec 4, 2009 ... HTTP client receives response message containing html file, ... one RTT to initiate **TCP connection**; one RTT for HTTP request and uses **TCP** to reliably transfer email message from client to server, port 25; direct transfer: **sending** How does callee advertise its IP address, port number, ...
ws.edu.isoc.org/data/2010/.../lecture-04-mon-tue-applications.ppt - [Similar](#)

22. [STUDY GUIDE For Network](#)

A **peer to peer network** is one in which lacks a dedicated server and every

Assuming the DHCP server isn't on fire or anything it will send out a DHCPACK with Each entry in the lmhosts file must be unique, have a valid IP address for the ... associated with the B-node implementation of NetBIOS over TCP/IP. ...
www.toggit.com/NetPlus/netxguide.htm - [Cached](#) - [Similar](#)

23. [Emerald FullText Article : HoNeY: leveraging the MHP to provide ...](#)

by G Portelli - [Cited by 1](#) - [Related articles](#)

Data carousels are mapped as file systems and mainly contain Java ... Within the present study, only network technologies based on TCP/IP ... unicast address with a packet containing its name, IP address, and port. in a foreign Wi-Fi network, but it can contact each node by connecting back to its home server ...
emeraldinsight.com/Insight/viewContentItem.dojsessionid...

24. [Peer-assisted networking using RTMFP groups in Flash Player 10.1 ...](#)

Everything from application-level video multicasting to swarming file the instance's IP address and port number when other Flash Player instances would ... it's up to you how to pass that group spec string to each P2P client. Send a message to a neighbor or local node nearest the specified group address: ...
www.adobe.com/devnet/.../articles/p2p_rtmfp_groups_print.html - [Cached](#)

25. [Computer Networking, Kurose Ch 2](#)

Jun 22, 1998 ... P2P file sharing. Multi-user network games ... Identifier includes both the IP address and port numbers HTTP client receives response message containing html file, ... time to transmit file initiate TCP connection RTT request file RTT direct transfer: sending server to receiving server ...
www.slideshare.net/dongants/computer-networking-kurose-ch-2 - [Cached](#)

26. [\[PPT\] 3rd Edition: Chapter 2](#)

File Format: Microsoft Powerpoint - [View as HTML](#)

identifier includes both IP address and port numbers associated with process on host. HTTP client sends HTTP request message (containing URL) into TCP data connection to transfer another file. control connection: "out of band" ... message from client to server, port 25; direct transfer: sending server to ...
www.csie.nctu.edu.tw/~shieyuan/course/network/2010Spring/.../Ch02.ppt

27. [MS TCP/IP and Windows 95 Networking](#)

In addition to IP addresses and subnet masks, for a TCP/IP client to access This file contains network name/network number mappings for # local networks. Specifies the number of times that TCP will retransmit a connect request ... Default: 1 (b-node) if no value is specified or no WINS servers are ...
technet.microsoft.com/en-us/library/cc723264.aspx - [Cached](#) - [Similar](#)

28. [\[PDF\] Architecture and Performance](#)

File Format: PDF/Adobe Acrobat - [Quick View](#)

Jun 22, 1998 ... the IP address and port numbers associated file initiate TCP connection. RTT request file. RTT file received another file. ■. Control connection: "out of band" ... client to server, port 25. ■ direct transfer: sending server to receiving server Vertex (node): state ...
icawww1.epfl.ch/sc250_2004/lecture_notes/sc250_04_3.pdf - [Similar](#)

29. [Enabling SIP-Based Applications in Ad Hoc Networks](#)


by N Banerjee - [Cited by 5](#) - [Related articles](#)

addresses and port numbers of endpoints. The IP address and port numbers exchanged ... as SUBSCRIBE, NOTIFY, MESSAGE, SEND, are typically request messages and are A P2P network is generally constructed as an overlay network over the ... Target SIP URI, the SIPREQ ID, and the Originator IP Address or Node ...
www.research.ibm.com/people/a/arup/winet-invited-paper.pdf - [Similar](#)

30. [\[PDF\] Trust in Peer-to-Peer content distribution protocols](#)

File Format: PDF/Adobe Acrobat - [Quick View](#)

by N Kuntze
this network each node can be addresses and also additional support protocols as
an out of band operation, the tracker protocol, and the peer wire protocol. In ... the
network is associated with a meta file. This file provides pB (e.g. IP and port), the
AIK certificate of pB and the access ticket. ...
sit.sit.fraunhofer.de/smv/publications/downloads/KuFuRuWISTP2010.pdf



sending a push request containing client ID, IP address, TCP/IP port number 

Search

[Search within results](#) - [Language Tools](#) - [Search Help](#) - [Dissatisfied? Help us improve](#) - [Try Google Experimental](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Privacy](#) - [About Google](#)